

# BLOCK PAVING SEALER

ACRYLIC WET LOOK CLEAR SEALER, SOLVENT BASED

## REPELS WATER, DIRT AND OILS, PROTECTS SURFACES AND ENHANCES THEIR APPEARANCE

### PERFORMANCE ADVANTAGES

- > Ready to use sealer and appearance enhancer
- > Protects and decorates new or old concrete, block paving or recently cleaned paving
- > Long lasting
- > Can be brush, roller or spray applied
- > Do not use if surface is damp or rain imminent

### USES

- > Ready for use.
- > Sealer and appearance enhancer for new or old concrete, block paving or recently cleaned paving.
- > Can be brush, roller or spray applied.
- > Do not use if surface is damp or if rain is imminent.

### COLOUR RANGE

- > Clear.

### PACK SIZE

- > 5 litre and 20 litre containers.

### SURFACE FINISH

- > Semi-gloss

### SPREADING RATE

- > Coverage is approximately 5 – 7 square metres per litre per coat but will vary depending upon application method, surface porosity and ambient conditions.



### DRYING TIME

- > Surface dry in 1-2 hours. Re-coatable overnight.

### SHELF LIFE

- > Up to 2 years if stored correctly in an unopened container.

### PREPARATION

Surfaces should be clean, dry and free from oil, grease, dust, laitence and any other deleterious materials.

**Previously painted or coated substrates**

**IT IS GOOD PRACTICE TO INSPECT AND CARRY OUT ADHESION TESTS ON ANY EXISTING COATING OR SUBSTRATE PRIOR TO APPLICATION OF THE COATING.**



## APPLICATION

- > Use as supplied without thinning down.
- > Do not apply in temperatures below 5°C or above 25°C and should not be subjected to extremes of temperature until completely dry.
- > The surface should be sectioned off to assist accurate coverage. Apply THIN uniform coats maintaining a wet edge but do not allow to puddle.
- > **It is important to undertake a representative test area to ensure that the product is suitable for your requirements prior to commencement of the project and assessed for final appearance, chemical resistance and wet & dry slip resistance. This is particularly important where the surface has previously been sealed.**
- > Application should ideally be by an airless sprayer designed for solvent based products but application by brush or roller is also suitable. During application care should be taken to protect adjacent areas and equipment from overspray.
- > Under normal conditions it will be touch dry within 1 - 2 hours and may be lightly trafficked in 24 hours.
- > All equipment should be cleaned using Britannia Special Solvent (Not White Spirit), xylene, or similar. Flush sprayers thoroughly. Always clean equipment in a well ventilated area.

## MAINTENANCE

- > Fungicidal Wash should be used every 6 to 12 months to control the surface of fungal and algal growth.
- > Maintenance coats can be applied when signs of wear appear. Thoroughly clean and dry surface before application

## SITE CONDITIONS

- > Sap from trees can discolour and darken the coating.

## PRECAUTIONS

- > **Flammable.** Keep away from sources of ignition.
- > Ensure good ventilation during application.
- > Wear gloves, goggles and suitable protective clothing.
- > In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- > Remove splashes from the skin with a recognised hand cleaner or plenty of soap and water.
- > Keep out of reach of children.
- > Do not use near fishponds.
- > Harmful to aquatic organisms. May cause long term adverse effects in the aquatic environments.
- > Do not breathe vapour or spray.
- > Do not empty into drains.

Good working practice should be followed and safety.

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

*As Britannia Paints Limited has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself.*

If in doubt regarding any of the above points, please contact our technical services department for advice.

**A Material Safety Data Sheet is available on request.**

*It is the users responsibility to ensure that this data sheet is current prior to using the product.*



Certificate Number 8516  
ISO 9001



Unit 7/8 King Street Trading Estate, Middlewich, Cheshire CW10 9LF  
T: 01606 834015 F: 01606 837006 E: sales@britanniapaints.co.uk www.britanniapaints.co.uk

Version 15 / June 2013