

# CONCRETE FLOOR SEALER

## SINGLE PACK CONCRETE FLOOR SEALER

**A 100% acrylic formulation concrete dustproofer with low viscosity for excellent penetration into the pores of the substrate**

### PERFORMANCE ADVANTAGES

- > Single pack
- > Low odour formulation
- > Very safe and easy to apply
- > Produces a dust-free concrete surface with a subtle sheen

### USES

- > Ideal for treatment of dusting concrete floors in factories, warehouses, kitchens, food processing areas, garages, workshops, production and plant areas.

### SUITABLE SUBSTRATES

- > Designed to penetrate and bind concrete, sand/cement floor screeds, blockwork and rendered walls.

### COLOUR RANGE

- > Milky-white when applied, turning to clear as curing takes place.

### PACK SIZE

- > 5L and 20L containers.



### SPREADING RATE

- > Because of its penetrating characteristics, the coverage of is subject to great variation depending on the porosity of the substrate. As a guide, the coverage is generally between 8-10m<sup>2</sup> per litre per coat.
- > The coverage of the second coat will normally be considerably more than the first.

### DRYING TIME

- > At least 1-2 hours in warm, dry, well-ventilated conditions, longer if cold and damp) before applying the second coat.

### SHELF LIFE

- > Up to 18 months if stored in dry conditions at temperatures between +5°C and +35°C. Storage at higher temperatures may reduce the shelf life.
- > Protect from frost.



## PREPARATION AND APPLICATION

**Floor areas must be clean, dry and free of all contamination.** The floor must be allowed to dry and cleaned and any dust or debris swept or vacuumed off. Wall surfaces to be sealed should be brushed dry to remove dust and loose material.

### **Stir well before use and do not thin.**

Britannia Concrete Floor Sealer may be applied using a soft brush or broom, a nylon pile roller or squeegee. A thin, even, puddle-free first coat should be applied, and this must be allowed to **DRY THOROUGHLY** (at least 1-2 hours in warm, dry, well-ventilated conditions, longer if cold and damp) before applying the second coat.

## CLEANING

Tools and equipment, hands and skin should be cleaned whilst material is still wet using soap and water.

## PRECAUTIONS

- > Keep out of reach of children.
- > In case of contact with eyes wash immediately with plenty of water.
- > Remove splashes from skin with soap and water or a recognised hand cleaner.
- > Protect from freezing.
- > Do not apply paint if there is a risk of heavy rain or frost.
- > Do not use near fishponds.

## SAFETY

Good working practice should be followed and safety/walking boards should be utilised where required.

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

*As Britannia Paints Limited has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself.*

**There is a Code of practice from FERFA-“Specification and use of Liquid Applied Waterproofing Systems” on [www.lrwa.org.uk](http://www.lrwa.org.uk) which can be consulted for general advice.**

If in doubt regarding any of the above points, please contact our technical services department for advice.

**A Material Safety Data Sheet is available on request.**

*It is the users responsibility to ensure that this data sheet is current prior to using the product.*



Certificate Number 8516  
ISO 9001



Unit 7/8 King Street Trading Estate, Middlewich, Cheshire CW10 9LF  
T: 01606 834015 F: 01606 837006 E: [sales@britanniapaints.co.uk](mailto:sales@britanniapaints.co.uk) [www.britanniapaints.co.uk](http://www.britanniapaints.co.uk)

Version 1 / August 2016