

ANTI-VANDAL PAINT

SOLVENT FREE, NON-DRYING, ECO-FRIENDLY

SOFT AND SLIPPERY NON-DRYING DETERRENT

PERFORMANCE ADVANTAGES

- > Especially formulated
- > Deters vandals and trespassers
- > For use on a wide range of structures
- > Stays soft and slippery

USES

For use on drain pipes, sills, tops of wall and fences, anywhere which may be used as a grip point to gain unauthorised access, electricity pylons to prevent access to dangerous areas, telegraph poles, lamp post to prevent climbing.

- > For brush or mitt application.
- > Anti Vandal paint is not recommended for use on surfaces in areas which are subject to legitimate daily contact. It is also recommended that it not be applied to sills, fall pipes, walls, etc., within 7 feet of the ground level, and it's presence should be clearly identified to the public with WARNING NOTICES.
- > Use in areas where temperatures do not normally exceed 30°C.
- > Porous surfaces must be sealed to prevent this product drying out - see Preparation.



COLOUR RANGE

- > Black.

PACK SIZE

- > 1lt, 2.5lt and 5lt pack sizes.

SPREADING RATE

- > 1.2 - 1.6m²/lt, this is largely dependent on thickness of coating and substrate to be painted.

DRYING TIME

- > Non drying system. **This product does not dry.**

SHELF LIFE

- > Up to 2 years if stored correctly in an unopened container.

PREPARATION

General

New and previously painted surfaces should be dry and free from loose and flaking material, dirt, grease wax, etc. Unpainted woodwork and steelwork should be primed with the appropriate primer.

Metal surfaces

Remove any loose material such as rust, scale, dirt, etc by thorough wire brushing and primed with a suitable primer prior to application of the Anti Vandal paint.

Porous surfaces

Porous surfaces such as Unpainted Wood or Brickwork should be sealed with a suitable primer/Sealer **to prevent this product drying out prior to application of the Anti Vandal paint.**

Smooth surfaces

Smooth surface should be roughened using coarse abrasive paper or by wire brushing prior to application of the Anti Vandal paint.

- > Mix well before use.
- > Apply Anti Vandal paint with a short haired brush or industrial mitt, smoothing to a uniform finish to the recommended spreading rate.
- > Must be applied no lower than 7 feet from the ground.
- > Do not thin the product.
- > Wear gloves during application and only apply to areas above arms reach.

CLEANING

- > Clean all equipment with white spirit immediately after use.

PRECAUTIONS

- > Keep out of reach of children.
- > In case of contact with eyes rinse immediately with plenty of water and seek medical advice.
- > Remove splashes from skin with a recognised hand cleaner.
- > To be applied on structures no less than two metres from the floor.
- > Do not use near fishponds.
- > Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environments.
- > Do not empty into drains.

SAFETY

- > Good working practice should be followed.
- > Apply only to areas safely above head height ,where accidental contact with persons or pets will not occur.

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

As Britannia Paints Limited has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself.

If in doubt regarding any of the above points, please contact our technical services department for advice.

A Material Safety Data Sheet is available on request.

It is the users responsibility to ensure that this data sheet is current prior to using the product.



Certificate Number 8516
ISO 9001



Unit 7/8 King Street Trading Estate, Middlewich, Cheshire CW10 9LF
T: 01606 834015 F: 01606 837006 E: sales@britanniapaints.co.uk www.britanniapaints.co.uk

Version 14 / July 2016