

STABILISING MASONRY SOLUTION

STABILISING SOLUTION FOR FRIABLE AND CHALKING SURFACES, SOLVENT BASED

PROVIDES EXCELLENT SUBSTRATE SUITABLE FOR DECORATION

PERFORMANCE ADVANTAGES

- > Solvent based, highly penetrating single pack, pliolite resin-based Acrylic solution
- > For application to friable and chalking surfaces
- > Produces a substrate suitable for further decoration

USES

Suitable for stabilising interior and exterior surfaces that are friable or chalking to produce a surface suitable for decoration.

- > Can be brush, roller or spray applied.

Not suitable for use under solvent based products except Britannia's Wallshield exterior wall coatings.

COLOUR RANGE

- > Clear Liquid.

PACK SIZE

- > 5L & 20L containers.

SPREADING RATE

- > As a guide between 120-160 square metres/20 litres (6-8 square metres/litre).

Depends greatly on the porosity of the surface – very porous material will obviously absorb more Stabilising Masonry Solution than close-grained masonry.



DRYING TIME

- > Surface dry in 1-2 hours.
- > Drying depends upon the thickness of the coating.
- > Re-coatable overnight.

SHELF LIFE

- > Up to 2 years if stored correctly in an unopened container.

PREPARATION

- > All surfaces must be dry and free from mould growth, dirt and grease.
- > Algal or Fungal deposits should first be removed by power washing the surface and then coated with Britannia's Fungicidal Wash Solution.



APPLICATION

Supplied ready for use by brush, roller or spray. Apply liberally to the substrate to allow for thorough penetration. On some surfaces a second coat may be required.

DO NOT OVER SEAL THE SURFACE

A high gloss indicates that the surface has been over sealed and these areas should be rubbed down prior to painting.

CLEANING

> Clean all equipment with white spirit after use.

PRECAUTIONS

- > **Flammable** keep away from sources of ignition.
- > Ensure good ventilation during application.
- > Wear gloves, goggles and suitable protective clothes.
- > In case of contact with eyes rinse immediately with plenty of water and seek medical advice.
- > Remove splashes from the skin with a recognised hand cleaner or plenty of soap and water.
- > Keep out of reach of children.
- > Do not use near fishponds.
- > Toxic to aquatic organisms. May cause long term adverse effects in the aquatic environments.
- > Do not empty into drains.

SAFETY

Good working practice should be followed and safety/walking boards should be utilised where required.

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

As Britannia Paints Limited has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself.

If in doubt regarding any of the above points, please contact our technical services department for advice.

A Material Safety Data Sheet is available on request.

It is the users responsibility to ensure that this data sheet is current prior to using the product.



Certificate Number 8516
ISO 9001



Unit 7/8 King Street Trading Estate, Middlewich, Cheshire CW10 9LF
T: 01606 834015 F: 01606 837006 E: sales@britanniapaints.co.uk www.britanniapaints.co.uk

Version 1 / Nov 2015